


Compiling Techniques

Lecture 13: SSA Optimizations and Rewriting

SSA simplifies Optimization Design



Reminder: Single Static Assignment (SSA) Form

*“A program is defined to be in **Single Static Assignment (SSA)** form if each variable is a target of exactly one assignment statement in the program text.”*

An important property from this definition is *referential transparency*:

“An expression is called referentially transparent if it can be replaced with its corresponding value (and vice-versa) without changing the program's behaviour”.

A Simple Program: Can we Optimize It?

```
print(42 + 8)
```



```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

```
choco.ir.call_expr(%2) ["func_name" = "print"]
```

A Simple Program: Can we Optimize It? Yes!

```
print(42 + 8)
```



```
%3 = choco.ir.literal() ["value" = 50 : !i32]  
choco.ir.call_expr(%3) ["func_name" = "print"]
```

What are the steps needed to optimize this program?

```
print(42 + 8)
```



```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

```
choco.ir.call_expr(%2) ["func_name" = "print"]
```

Step 1: Constant Folding

```
print(42 + 8)
```



```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
%3 = choco.ir.literal() ["value" = 50 : !i32]
choco.ir.call_expr(%3) ["func_name" = "print"]
```

Step 2: Dead Code Elimination


```
print(42 + 8)
```



```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
%3 = choco.ir.literal() ["value" = 50 : !i32]
choco.ir.call_expr(%3) ["func_name" = "print"]
```


Constant Folding

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.binary_expr(%2, %3) ["op" = "+"]
```



Constant Folding

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.binary_expr(%2, %3) ["op" = "+"]
```




- 1) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.

Constant Folding

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.literal() ["value" = 50 : !i32]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.binary_expr(%2, %3) ["op" = "+"]
```

42

8




- 1) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 2) Compute result and replace `binary_expr` with literal of value result.

Constant Folding

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.literal() ["value" = 50 : !i32]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.binary_expr(%2, %3) ["op" = "+"]
```

42 8



- 1) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 2) Compute result and replace `binary_expr` with literal of value result.
- 3) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.

Constant Folding

42

8

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.literal() ["value" = 50 : !i32]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.literal() ["value" = 55 : !i32]
```

50

5

55

- 1) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 2) Compute result and replace `binary_expr` with literal of value result.
- 3) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 4) Compute result and replace `binary_expr` with literal of value result.

Constant Folding

42

8

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.literal() ["value" = 50 : !i32]
%3 = choco.ir.literal() ["value" = 5 : !i32]
%4 = choco.ir.literal() ["value" = 55 : !i32]
```

50

5

55


- 1) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 2) Compute result and replace `binary_expr` with literal of value result.
- 3) Find `binary_expr` where the `lhs` is a constant literal and the `rhs` is a constant literal.
- 4) Compute result and replace `binary_expr` with literal of value result.



Repeat
(if needed)


Dead Code Elimination

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```



Dead Code Elimination

```
%0 = choco.ir.literal() ["value" = 42 : !i32]  
%1 = choco.ir.literal() ["value" = 8 : !i32]  
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```



- 1) Find [binary_expr](#) without users

Dead Code Elimination

42

8

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

- 1) Find `binary_expr` without users
- 2) Delete `binary_expr`

Dead Code Elimination

42

8

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

- 1) Find `binary_expr` without users
- 2) Delete `binary_expr`
- 3) Find `literal` without users

Dead Code Elimination

42

```
%0 = choco.ir.literal() ["value" = 42 : !i32]  
%1 = choco.ir.literal() ["value" = 8 : !i32]  
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

- 1) Find `binary_expr` without users
- 2) Delete `binary_expr`
- 3) Find `literal` without users
- 4) Delete `literal`

Dead Code Elimination

42

```
%0 = choco.ir.literal() ["value" = 42 : !i32]  
%1 = choco.ir.literal() ["value" = 8 : !i32]  
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```


- 1) Find `binary_expr` without users
- 2) Delete `binary_expr`
- 3) Find `literal` without users
- 4) Delete `literal`
- 5) Find `literal` without users

Dead Code Elimination

```
%0 = choco.ir.literal() ["value" = 42 : !i32]
%1 = choco.ir.literal() ["value" = 8 : !i32]
%2 = choco.ir.binary_expr(%0, %1) ["op" = "+"]
```

- 1) Find `binary_expr` without users
- 2) Delete `binary_expr`
- 3) Find `literal` without users
- 4) Delete `literal`
- 5) Find `literal` without users
- 6) Delete `literal`

Pattern Rewriting aka. Peephole Optimizations



PatternRewriteWalker

walk_reverse : bool

GreedyRewritePatternApplier

RewritePattern

Match

Replace

RewritePattern

Match

Replace

RewritePattern

Match

Replace

RewritePattern

Match

Replace

Match and Rewrite: Constant Folding

```
@dataclass
class BinaryExprRewriter(RewritePattern):

    @op_type_rewrite_pattern
    def match_and_rewrite(self, expr: BinaryExpr, rewriter: PatternRewriter) -> None:
        if expr.op.data == '+':
            if isinstance(expr.lhs.op, Literal) and
               isinstance(expr.rhs.op, Literal):
                lhs_value = expr.lhs.op.value.parameters[0].data
                rhs_value = expr.rhs.op.value.parameters[0].data
                result_value = lhs_value + rhs_value
                new_constant = Literal.get(result_value)
                rewriter.replace_op(expr, [new_constant])

Return
```

Apply on Full Module

```
def choco_flat_constant_folding(ctx: MLContext, module: ModuleOp)
    -> ModuleOp:

    walker = PatternRewriteWalker(GreedyRewritePatternApplier([
        BinaryExprRewriter(),
    ]))

    walker.rewrite_module(module)
    return module
```

Match and Rewrite: Dead Code Implementation

```
@dataclass
class LiteralRewriter(RewritePattern):

    @op_type_rewrite_pattern
    def match_and_rewrite(self, literal: Literal, rewriter: PatternRewriter) -> None:
        if len(literal.results[0].uses) == 0:
            rewriter.replace_op(literal, [], [None])
        return

@dataclass
class BinaryExprRewriter(RewritePattern):

    @op_type_rewrite_pattern
    def match_and_rewrite(self, expr: BinaryExpr, rewriter: PatternRewriter) -> None:
        if len(expr.results[0].uses) == 0:
            rewriter.replace_op(expr, [], [None])

        return
```

Apply on Full Module

```
def choco_dead_code_elimination(ctx: MLContext, module: ModuleOp)
    -> ModuleOp:

    walker = PatternRewriteWalker(GreedyRewritePatternApplier([
        LiteralRewriter(),
        BinaryExprRewriter(),
    ]), walk_reverse=True)

    walker.rewrite_module(module)
    return module
```

