



Advanced Database Systems

Spring 2026

Lecture #02: SQL

If you require this document in an alternative format, such as large print or a coloured background, please contact milos.nikolic@ed.ac.uk

1

SQL HISTORY

Developed @ IBM Research in the 1970s

System R project

Originally "SEQUEL": Structured English Query Language

Commercialised/popularised in the 1980s

Adopted by Oracle in the late 1970s

IBM released DB2 in 1983

ANSI standard in 1986. ISO in 1987

Structured Query Language

Current standard is SQL:2023

2

SQL's PERSISTENCE

4

52 years old!

1974 – Developed at IBM by Donald D. Chamberlin and Raymond F. Boyce

Questioned repeatedly

90's: Object-Oriented DBMS (OQL, etc.)

2000's: XML (Xquery, Xpath, XSLT)

2010's: NoSQL & MapReduce

SQL keeps re-emerging as the standard

Even Hadoop, Spark etc. mostly used via SQL

May not be perfect, but it is useful

4

SQL PROS AND CONS

5

Declarative!

Say what you want, not how to get it

Implemented widely

With varying levels of efficiency, completeness

Most DBMSs support at least SQL-92

Constrained

Not targeted at Turing-complete tasks

Feature-rich

Many years of added features

Extensible: callouts to other languages, data sources

5

OUTLINE

- Relational Terminology
- Single-table Queries
- Aggregations + Group By
- Joins
- Nested Queries

6

6

RELATIONAL TERMINOLOGY

Database: Set of named relations

Relation (Table):

Schema: description ("metadata")

`Student(sid: int, name: text, dept: text)`

Instance: collection of data satisfying the schema

Tuple (record, row) 

Attribute (field, column) 

sid	name	dept
12344	Jones	CS
12355	Smith	Physics
12366	Gold	CS

7

RELATIONAL TABLES

8

Schema is fixed

Unique attribute names, attribute types are **atomic**

`Student(sid: int, name: text, dept: text)`

Instances can change often

In SQL, an instance is a **multiset** (bag) of tuples

name	dept	age
Jones	CS	18
Smith	Physics	21
Jones	CS	18

8

SQL LANGUAGE

9

Three sublanguages

DDL Data Definition Language *Define and modify schema*

DML Data Manipulation Language *Write queries intuitively*

DCL Data Control Language *Control access to data*

RDBMS responsible for efficient evaluation

Choose and run algorithms for declarative queries

Choice of algorithm must not affect query answer

9

EXAMPLE DATABASE

Student(sid, name, dept, age)

sid	name	dept	age
12344	Jones	CS	18
12355	Smith	Physics	23
12366	Gold	CS	21

Course(cid, name, year)

cid	name	year
INF-11199	Advanced Database Systems	2020
INF-10080	Introduction to Databases	2020
INF-11122	Foundations of Databases	2019
INF-11007	Data Mining and Exploration	2019

Enrolled(sid, cid, grade)

sid	cid	grade
12344	INF-10080	65
12355	INF-11199	72
12355	INF-11122	61
12366	INF-10080	80
12344	INF-11199	53

10

BASIC SINGLE-TABLE QUERIES

```
SELECT [DISTINCT] <column expression list>
  FROM <single table>
  [WHERE <predicate>]
```

```
SELECT *
  FROM Student
  WHERE age = 18
```

Get all 18-year-old students

```
SELECT DISTINCT cid
  FROM Enrolled
  WHERE grade > 95
```

Get IDs of courses with grades > 95

Simplest version is straightforward

Produce all tuples in the table that match the predicate

Output the expressions in the **SELECT** list

Expression can be a column reference, or
an arithmetic expression over column refs

DISTINCT removes duplicate rows before output

11

10

ORDER BY

ORDER BY <column*> [ASC|DESC]

Sort the output tuples by the values in one or more of their columns

```
SELECT sid, grade FROM Enrolled
  WHERE cid = 'INF-11199'
  ORDER BY grade
```

sid	grade
12344	53
12399	72
12355	72
12311	76

Ascending order by default, but can be overridden

Can mix and match, lexicographically

```
SELECT sid, grade FROM Enrolled
  WHERE cid = 'INF-11199'
  ORDER BY grade DESC, sid ASC
```

sid	grade
12311	76
12355	72
12399	72
12344	53

12

LIMIT

LIMIT <count> [<offset>]

Limit the # of tuples returned in the output

```
SELECT sid, grade FROM Enrolled
  WHERE cid = 'INF-11199'
  ORDER BY grade LIMIT 3
```

sid	grade
12344	53
12399	72
12355	72

Typically used with **ORDER BY**

Otherwise the output is non-deterministic, depends on the algo for query processing

Can set an offset to skip first records

```
SELECT sid, grade FROM Enrolled
  WHERE cid = 'INF-11199'
  ORDER BY grade LIMIT 3 OFFSET 1
```

sid	grade
12399	72
12355	72
12311	76

12

13

AGGREGATES

Functions that return a summary (aggregate) of some arithmetic expression from a bag of tuples

Get the average age of CS students

```
SELECT AVG(age) AS avg_age
  FROM Student WHERE dept = 'CS'
    avg_age
    20.5
```

Get the average age and # of CS students

```
SELECT AVG(age) AS avg_age,
       COUNT(sid) AS cnt
  FROM Student WHERE dept = 'CS'
    avg_age  cnt
    20.5    153
```

Aggregate functions can only be used in the **SELECT** list

Other aggregates: **SUM**, **COUNT**, **MIN**, **MAX**

14

GROUP BY

Get the average age per department

```
SELECT dept, AVG(age) AS avg_age
  FROM Student
 GROUP BY dept
```

dept	avg_age
CS	20.5
Physics	21.1
Maths	19.8

Partition table into groups with the same **GROUP BY** column values

Can group by a list of columns

Produce an aggregate result per group

Cardinality of output = # of distinct group values

Can put grouping columns in the **SELECT** output list

14

15

GROUP BY

Non-aggregated values in **SELECT** output clause must appear in **GROUP BY** clause

```
SELECT dept, name, AVG(age)
  FROM Student
 GROUP BY dept
```



```
SELECT dept, name, AVG(age)
  FROM Student
 GROUP BY dept, name
```



16

FILTER GROUPS

Get the average age per department

```
SELECT dept, AVG(age) AS avg_age
  FROM Student
 GROUP BY dept
```

dept	avg_age
CS	20.5
Physics	21.1
Maths	19.8

Get departments with average student age above 21

```
SELECT dept, AVG(age) AS avg_age
  FROM Student
 WHERE avg_age > 21
 GROUP BY dept
```



dept	avg_age
Physics	21.1

16

17

HAVING

Get departments with average student age above 21

```
SELECT dept, AVG(age) AS avg_age
  FROM Student
 GROUP BY dept
 HAVING AVG(age) > 21
```

HAVING filters results **after** grouping and aggregation

Hence can contain anything that could go in the SELECT list

i.e., GROUP BY columns or aggregates (e.g., COUNT(*) > 5)


HAVING can only be used in aggregate queries

It's an optional clause

18

CONCEPTUAL SQL EVALUATION

```
SELECT [DISTINCT] <column expression list>
  FROM <single table>
  [WHERE <predicate>]
  [GROUP BY <column list> [HAVING <predicate>]]
  [ORDER BY <column list>] [LIMIT <count>]
```




Does not imply the query will actually be evaluated this way!

19

MULTIPLE-TABLE QUERIES

```
SELECT [DISTINCT] <column expression list>
  FROM <table1 [AS t1], ..., tableN [AS tn]>
  [WHERE <predicate>]
  [GROUP BY <column list> [HAVING <predicate>]]
  [ORDER BY <column list>] [LIMIT <count>]
```



This evaluation strategy is almost always inefficient!

20

JOIN QUERY

Get the names and grades of students in INF-11199

```
SELECT S.name, E.grade
  FROM Student AS S, Enrolled AS E
 WHERE S.sid = E.sid
   AND E.cid = 'INF-11199'
```

name	grade
Smith	72
Jones	53

Student(sid, name, dept, age)

sid	name	dept	age
12344	Jones	CS	18
12355	Smith	Physics	23
12366	Gold	CS	21

Enrolled(sid, cid, grade)

sid	cid	grade
12344	INF-10080	65
12355	INF-11199	72
12355	INF-11122	61
12366	INF-10080	80
12344	INF-11199	53

Declarative computation

Let the DBMS figure out how to compute this query

Possible options:

- 1) Cross product → filter on sid & cid → projection
- 2) Filter on cid → cross product → filter on sid → projection
- 3) Something else?

20

21

JOIN QUERY – ANOTHER SYNTAX

22

Get the names and grades of students in INF-11199

```
SELECT S.name, E.grade
  FROM Student AS S, Enrolled AS E
 WHERE S.sid = E.sid
   AND E.cid = 'INF-11199'
```

All 3 queries are equivalent

```
SELECT S.name, E.grade
  FROM Student S INNER JOIN Enrolled E
    ON S.sid = E.sid
 WHERE E.cid = 'INF-11199'
```

Inner join what we've learned so far
INNER is optional here

```
SELECT S.name, E.grade
  FROM Student S NATURAL JOIN Enrolled E
 WHERE E.cid = 'INF-11199'
```

NATURAL means equi-join for pairs of attributes with the same name

JOIN VARIANTS

```
SELECT <column list>
  FROM <table>
    [INNER | NATURAL | { LEFT | RIGHT | FULL } OUTER] JOIN
      ON <qualification list>
    WHERE ...
```

The different types of **outer** joins determine what we do with rows that don't match the join condition

22

23

LEFT OUTER JOIN

24

Student

sid	name	dept	age
121	Jones	CS	18
122	Smith	Physics	19
123	Gold	CS	21

```
SELECT S.name, E.grade
  FROM Student S LEFT OUTER JOIN Enrolled E
    ON S.sid = E.sid
```

Return all matched rows & preserve all unmatched rows from the table on the **left** of the join clause

Use **NULLs** in fields of non-matching tuples

Enrolled

sid	cid	grade
121	INF-10080	65
123	INF-11199	72
121	INF-11122	61
201	INF-11199	53

RIGHT OUTER JOIN

25

Student

sid	name	dept	age
121	Jones	CS	18
122	Smith	Physics	19
123	Gold	CS	21

```
SELECT S.name, E.grade
  FROM Student S RIGHT OUTER JOIN Enrolled E
    ON S.sid = E.sid
```

Enrolled

sid	cid	grade
121	INF-10080	65
123	INF-11199	72
121	INF-11122	61
201	INF-11199	53

Return all matched rows & preserve all unmatched rows from the table on the **right** of the join clause

24

25

FULL OUTER JOIN

26

Student

sid	name	dept	age
121	Jones	CS	18
122	Smith	Physics	19
123	Gold	CS	21

```
SELECT S.name, E.grade
  FROM Student S FULL OUTER JOIN Enrolled E
        ON S.sid = E.sid
```

Enrolled

sid	cid	grade
121	INF-10080	65
123	INF-11199	72
121	INF-11122	61
201	INF-11199	53

name	grade
Jones	65
Jones	61
Gold	72
Smith	NULL
NULL	53

Return all matched & unmatched rows from the tables on **both** sides of the join clause

26

NESTED QUERIES

27

Queries containing other queries

They are often difficult to optimise

Inner queries can appear (almost) anywhere in query

Get the names of students enrolled in any course

Outer Query →

```
SELECT S.name FROM Student S
  WHERE S.sid IN
        ( SELECT E.sid FROM Enrolled E )
```

 Inner Query

27

NESTED QUERIES

28

Get the names of students in INF-11199

```
SELECT S.name FROM Student S
  WHERE S.sid IN (
    SELECT E.sid FROM Enrolled E
      WHERE E.cid = 'INF-11199'
  )
```

“S.sid in the set of students that take INF-11199”

This is a bit odd, but it is equivalent:

```
SELECT S.name FROM Student S
  WHERE EXISTS (
    SELECT E.sid FROM Enrolled E
      WHERE E.cid = 'INF-11199'
        AND S.sid = E.sid
  )
```

Nested query with correlation on sid

Correlated subquery is recomputed for each Student tuple

28

MORE ON SET-COMPARISON OPERATORS

29

Seen so far: **IN, EXISTS**

Can also have: **NOT IN, NOT EXISTS, op ALL, op ANY**

where **op** is a standard comparison operator (=, <>, !=, >, >=, <, <=)

ALL → Must satisfy expression for all rows in subquery

ANY → Must satisfy expression for at least one row in subquery

IN → Equivalent to '**= ANY()**'

NOT IN → Equivalent to '**!= ALL()**'

EXISTS → At least one row is returned

Get the names of students in INF-11199

```
SELECT S.name FROM Student S
  WHERE S.sid = ANY (
    SELECT E.sid FROM Enrolled E
      WHERE E.cid = 'INF-11199'
  )
```

29

SUMMARY

This was a crash course on SQL

Many aspects not covered though, only essential

SQL is a declarative language

Somebody must translate SQL to algorithms... but how?

The data structures and algorithms that make SQL possible also power:

NoSQL, data mining, scalable ML analytics,...

A toolbox for scalable computing!

That fun begins next week