



Advanced Database Systems

Spring 2026

Lecture #05: Buffer Management



R&G: Chapter 9.4

If you require this document in an alternative format, such as large print or a coloured background, please contact milos.nikolic@ed.ac.uk

1

BUFFER MANAGEMENT


Transfer data between disk and memory



2

BUFFER MANAGEMENT


Buffer pool: in-memory cache of disk pages, partitioned into **frames**



3

BUFFER MANAGEMENT: PAGE REQUEST

Ensures requested page is in memory upon return




3

4

2

BUFFER MANAGEMENT: PAGE RELEASE

Higher levels need to explicitly "release" a page



5

OPEN QUESTIONS

What if the buffer pool has no space for a new page?

Use a **replacement policy** to decide which page to evict

What if a page gets modified? How will the buffer manager find out?

Dirty flag on page: Is page modified or not, set during release by higher levels

When evicting a dirty page, write it back to disk via disk space manager

How many users are concurrently using a page?

Pin counter per frame: # of concurrent users of the page


If pin counter = 0, the page is a candidate for replacement

6

BUFFER MANAGER STATE

Buffer pool

Large range of memory allocated at DBMS server boot time (MBs-GBs)



Buffer manager metadata:

Smallish array in memory allocated at DBMS server boot time

Page ID lookups need to be fast

Keep an in-memory index (hash table) on PageId

FrameId	PageId	Dirty?	Pin Count
1	1	N	0
2	2	Y	1
3	8	N	0
4	6	N	2
5	4	N	0
6	5	N	0

7

PROPER PIN/UNPIN NESTING

Database users (e.g., transactions) must properly "bracket" any page operation using **pin** and **unpin**

A read-only transaction

```
a = pin(pageno)
[...]
    read data on page at memory address a
[...]
unpin(pageno, false)
```

Proper bracketing useful to keep a count of active users of a page

8

PIN IMPLEMENTATION

```
Function pin(pageno)
  if buffer pool already contains pageno then
    f = find frame containing pageno
    f.pinCount = f.pinCount + 1
    return address of frame f
  else
    f = select a free frame if buffer is not full or
        a victim frame using the replacement policy
    if f.isDirty then
      write frame f to disk
      read page pageno from disk into frame f
    f.pinCount = 1
    f.isDirty = false
  return address of frame f
```

Invariant:
f.pinCount = 0

9

UNPIN IMPLEMENTATION

```
Function unpin(pageno, dirty)
  f = find frame containing pageno
  f.pinCount = f.pinCount - 1
  f.isDirty = f.isDirty || dirty
```

Why don't we check if pageno is in the buffer pool ?

Why don't we write back to disk during unpin?

9

10

ADVANCED QUESTIONS

Concurrent operations on a page

1. The same page p is requested by more than one transaction (i.e., pin counter of $p > 1$)
2. Those transactions perform **conflicting writes** on p

Solved by **Concurrency Control** module

... before the page is unpinned

Buffer manager may assume everything is in order whenever it gets an `unpin(p, true)` call

What if system crashes before write-back?

Solved by **Recovery** module

More about CC & Recovery later

11

BUFFER REPLACEMENT POLICIES

Page is chosen for replacement by a **replacement policy**:

Least Recently Used (LRU), Clock

Most Recently Used (MRU)

Others: Random, Toss-Immediate, FIFO, LRU-K

Policy can have big impact on #I/Os

Effectiveness depends on the **access patterns** in high-level code

No single policy handles all possible scenarios well

11

12

10

LEAST RECENTLY USED (LRU)

Very common policy: intuitive and simple

Track time each frame was last unpinned (end of use)

Replace the frame which was least recently used (lowest last used time)

Pinned frames are not available to replace

FrameId	PageId	Dirty?	Pin Count	Last Used
1	1	N	0	43
2	2	Y	1	21
3	8	N	0	22
4	6	N	2	11
5	4	N	0	24
6	5	N	0	15

Pinned frames
Next-to-replace frame

14

LEAST RECENTLY USED (LRU)

Good for repeated accesses to popular pages (temporal locality)

Unpopular pages accessed a while ago are more likely to be replaced

Can be **costly**. Why?

Need to "find min" on the last used attribute

Naive: Scan table to find the unpinned frame with the lowest last used time (linear time)

Better: Use priority queues to keep frames in sorted order (log time)

Priority queues can still be expensive as page accesses are frequent

Approximate LRU: CLOCK policy

14

15

CLOCK REPLACEMENT POLICY

Each frame has a **reference bit**

Set **referenced** = 1 when pin count increases


N frames arranged in a circular buffer with a "clock hand"

Clock hand = next page to consider for eviction

```
while victim is not found:
    if frames[hand].pinCount == 0 then
        if frames[hand].referenced == 1 then
            frames[hand].referenced = 0
        else
            victim = address of frames[hand]
    hand = (hand + 1) mod N
```

Invoked when the pool is full and we need to evict a page


16



CLOCK POLICY STATE: EXPLICIT & ILLUSTRATED

FrameId	PageId	Dirty?	Pin Count	Ref Bit
1	1	N	1	1
2	3	N	1	1
3	2	N	0	1
4	8	N	0	0
5	4	N	0	0
6	5	N	0	1

Clock Hand
2



16

17

17

CLOCK POLICY: READ PAGE 10 (CONT.)

Current frame not pinned

Reference bit unset


Replace page 8 by page 10

Set pinned

Set reference bit

Advance clock

Return pointer to page 10



22

REPLACEMENT POLICIES CAN FAIL

LRU and CLOCK are susceptible to **sequential flooding**

Scans pollute the buffer with pages that might not be needed soon

For scans the most recently used page is the most unneeded page!

Example 1

A buffer pool consists of 6 frames. A query repeatedly scans relation R.

Case 1: Let the size of relation R be 6 pages. How many I/O do you expect?

Case 2: Now let the size of relation R be 7 pages. How many I/O do you expect?

26


22

REPEATED SCAN (LRU)

The buffer pool consists of 6 frames

Assume the frames are initially empty

Case 1: R consists of 6 pages



27

REPEATED SCAN (LRU)


The buffer pool consists of 6 frames

Assume the frames are initially empty

Case 1: R consists of 6 pages

First 6 requests are unavoidable misses

Subsequent requests P1-P6 are all **hits**!



28

27

26

REPEATED SCAN (LRU)

The buffer pool consists of **6 frames**


Assume the frames are initially empty

Case 1: R consists of 6 pages

First 6 requests are unavoidable misses

Subsequent requests P1-P6 are all **hits!**

Case 2: R consists of 7 pages



29

REPEATED SCAN (LRU)

The buffer pool consists of **6 frames**

Assume the frames are initially empty


Case 1: R consists of 6 pages

First 6 requests are unavoidable misses

Subsequent requests P1-P6 are all **hits!**

Case 2: R consists of 7 pages

P7 evicts P1, restart scan



30

29

REPEATED SCAN (LRU)

The buffer pool consists of **6 frames**

Assume the frames are initially empty

Case 1: R consists of 6 pages


First 6 requests are unavoidable misses

Subsequent requests P1-P6 are all **hits!**

Case 2: R consists of 7 pages

P7 evicts P1, restart scan,
P1 evicts P2, P2 evicts P3, etc.

All subsequent page requests are **misses!**




31

REPEATED SCAN (MRU)

Most Recently Used (MRU)

First 6 requests are unavoidable misses



32

31


REPEATED SCAN (MRU)

Most Recently Used (MRU)

First 6 requests are unavoidable misses

Request for P7 evicts P6

After restart, P1-P5 requests are all **hits!**



33

REPEATED SCAN (MRU)

Most Recently Used (MRU)

First 6 requests are unavoidable misses


Request for P7 evicts P6

After restart, P1-P5 requests are all **hits!**

Request for P6 evicts P5

Next 5 requests are also **hits!**

and so on...



34

33

34

BEST REPLACEMENT POLICY?

LRU suffers from sequential flooding

But good for random access (hot vs. cold data)

LRU-K variant:

Consider history of the last K references

Evict the page whose K-th most recent access is furthest away in the past

MRU better fit for repeated sequential scans

Repeated scans are very common in database workloads (e.g., nested-loops join)

Hybrids are not uncommon in modern DBMSs

PostgreSQL uses CLOCK but handles sequential scans separately

35

BUFFER MANAGEMENT IN PRACTICE

Priority hints

The DBMS knows the context of each page during query execution

It can provide hints to the buffer manager on whether a page is important or not

Page fixing & hating:

Request to **fix** a page as it may be useful soon (e.g., nested-loop joins)

Request to **hate** a page as it may not be accessed soon (e.g., pages in a sequential scan)

Partitioned buffer pools

Separate pools for tables, indexes, logs, etc.

35

36

36

BUFFER MANAGEMENT IN PRACTICE

Page Prefetching

Ask disk space manager for a run of sequential pages

E.g., on request for Page 1, ask for Pages 2-5

Why does this help?

Amortise random I/O overhead

Allow computation while I/O continues in background
(disk and CPU are “parallel devices”)

37

WHY NOT USE THE OS?

Wait! Doesn't the filesystem (OS) manage buffers and pages too?

Yes, but:

DBMS requires ability to force flushing pages to disk in correct order

Required for recovery, as discussed later

DBMS has more information about query plans and access patterns of operators

Affects both page replacement and prefetching

Portability: different filesystem, different behaviour

The OS is not your friend!

38

38

SUMMARY

Buffer Manager

Mediator between storage and main memory

Maps disk page IDs to RAM addresses

Ensures each requested page is “pinned” in RAM

To be (briefly) manipulated in-memory


And then unpinned by the caller!

Attempts to minimize “cache misses”

By replacing pages unlikely to be referenced

By prefetching pages likely to be referenced

39



39