# Elements of Programming Languages

## Lecture 5: Functions and recursion

James Cheney

University of Edinburgh

November 12, 2026

# Overview

- So far, we've covered
  - arithmetic
  - booleans, conditionals (`if then else`)
  - variables and simple binding (`let`)
- $L_{Let}$ allows us to compute values of expressions
  - and use variables to store intermediate values
  - but not to define *computations* on unknown values.
  - That is, there is no feature analogous to Haskell's functions, Scala's `def`, or methods in Java.
- Today, we consider *functions* and *recursion*

# Named functions

- A simple way to add support for functions is as follows:

$$e ::= \cdots \mid f(e) \mid \texttt{let fun } f(x : \tau) = e_1 \texttt{ in } e_2$$

- Meaning: Define a function called $f$ that takes an argument $x$ and whose result is the expression $e_1$.
- Make $f$ available for use in $e_2$.
- (That is, the scope of $x$ is $e_1$, and the scope of $f$ is $e_2$.)
- This is pretty limited:
  - for now, we consider one-argument functions only.
  - no recursion
  - functions are not first-class "values" (e.g. can only call $f$, can't pass a function as an argument to another)

# Examples

- We can define a squaring function:

$$\texttt{let fun } \mathit{square}(x : \texttt{int}) = x \times x \texttt{ in } \cdots$$

- or (assuming inequality tests) absolute value:

$$\texttt{let fun } \mathit{abs}(x : \texttt{int}) = \texttt{if } x < 0 \texttt{ then } -x \texttt{ else } x \texttt{ in } \cdots$$

# Types for named functions

- We introduce a *type constructor* $\tau_1 \to \tau_2$, meaning "the type of functions taking arguments in $\tau_1$ and returning $\tau_2$"
- We can typecheck named functions as follows:

$$\frac{\Gamma, x{:}\tau_1 \vdash e_1 : \tau_2 \quad \Gamma, f{:}\tau_1 \to \tau_2 \vdash e_2 : \tau}{\Gamma \vdash \texttt{let fun } f(x : \tau_1) = e_1 \texttt{ in } e_2 : \tau}$$

$$\frac{\Gamma(f) = \tau_1 \to \tau_2 \quad \Gamma \vdash e : \tau_1}{\Gamma \vdash f(e) : \tau_2}$$

- For convenience, we just use a single environment $\Gamma$ for both variables and function names.

# Example

Typechecking of $abs(-42)$

$$\dfrac{\dfrac{\dfrac{\Gamma(x) = \texttt{int}}{\Gamma \vdash x : \texttt{int}} \quad \dfrac{}{\Gamma \vdash 0 : \texttt{int}}}{\Gamma \vdash x < 0 : \texttt{bool}} \quad \dfrac{\dfrac{\Gamma(x) = \texttt{int}}{\Gamma \vdash x : \texttt{int}}}{\Gamma \vdash -x : \texttt{int}} \quad \dfrac{\Gamma(x) = \texttt{int}}{\Gamma \vdash x : \texttt{int}}}{\Gamma \vdash \texttt{if } x < 0 \texttt{ then } -x \texttt{ else } x : \texttt{int}}$$

$$\dfrac{\dfrac{\vdots}{\Gamma \vdash e_{abs} : \texttt{int}} \quad \dfrac{\dfrac{}{abs{:}\texttt{int} \to \texttt{int} \vdash -42 : \texttt{int}}}{abs{:}\texttt{int} \to \texttt{int} \vdash abs(-42) : \texttt{int}}}{\vdash \texttt{let fun } abs(x : \texttt{int}) = e_{abs} \texttt{ in } abs(-42) : \texttt{int}}$$

where $e_{abs} = \texttt{if } x < 0 \texttt{ then } -x \texttt{ else } x$ and $\Gamma = x{:}\texttt{int}$.

# Semantics of named functions

- We can define rules for evaluating named functions as follows.
- First, let $\delta$ be an environment mapping function names $f$ to their "definitions", which we'll write as $\langle x \Rightarrow e \rangle$.
- When we encounter a function definition, add it to $\delta$.

$$\frac{\delta[f \mapsto \langle x \Rightarrow e_1 \rangle], e_2 \Downarrow v}{\delta, \texttt{let fun } f(x : \tau) = e_1 \texttt{ in } e_2 \Downarrow v}$$

- When we encounter an application, look up the definition and evaluate the body with the argument value substituted for the argument:

$$\frac{\delta, e_0 \Downarrow v_0 \quad \delta(f) = \langle x \Rightarrow e \rangle \quad \delta, e[v_0/x] \Downarrow v}{\delta, f(e_0) \Downarrow v}$$

# Examples

Evaluation of $abs(-42)$

$$\dfrac{\dfrac{\delta, -42 < 0 \Downarrow \texttt{true} \quad \delta, -(-42) \Downarrow 42}{\delta, \texttt{if } -42 < 0 \texttt{ then } -(-42) \texttt{ else } -42 \Downarrow 42} \qquad \dfrac{\vdots}{\delta, e_{abs}[-42/x] \Downarrow 42}}{\dfrac{\delta, -42 \Downarrow -42 \quad \delta(abs) = \langle x \Rightarrow e_{abs} \rangle \quad \delta, abs(-42) \Downarrow 42}{\texttt{let fun } abs(x : \texttt{int}) = e_{abs} \texttt{ in } abs(-42) \Downarrow 42}}$$

where $e_{abs} = \texttt{if } x < 0 \texttt{ then } -x \texttt{ else } x$ and
$\delta = [abs \mapsto \langle x \Rightarrow e_{abs} \rangle]$

# Static vs. dynamic scope

- The terms *static* and *dynamic* scope are sometimes used.
- In **static scope**, the scope and binding occurrences of all variables can be determined from the program text, **without** actually running the program.
- In **dynamic scope**, this is not necessarily the case: the scope of a variable can depend on the context in which it is evaluated **at run time**.

# Static vs. dynamic scope

- Function bodies can contain free variables. Consider:

$$\begin{array}{l}\texttt{let } x = 1 \texttt{ in} \\ \texttt{let fun } f(y : \texttt{int}) = x + y \texttt{ in} \\ \texttt{let } x = 10 \texttt{ in } f(3)\end{array}$$

- Here, $x$ is bound to 1 at the time $f$ is defined, but re-bound to 10 when by the time $f$ is called.
- There are two reasonable-seeming result values, depending on which $x$ is *in scope*:
  - **Static scope** uses the binding $x = 1$ present when $f$ is **defined**, so we get $1 + 3 = 4$.
  - **Dynamic scope** uses the binding $x = 10$ present when $f$ is **used**, so we get $10 + 3 = 13$.

# Dynamic scope breaks type soundness

- But what if we do this:

$$\begin{array}{l}\texttt{let } x = 1 \texttt{ in} \\ \texttt{let fun } f(y : \texttt{int}) = x + y \texttt{ in} \\ \texttt{let } x = \texttt{true} \texttt{ in } f(3)\end{array}$$

- When we typecheck $f$, $x$ is an integer, but it is re-bound to a boolean by the time $f$ is called.
- The program as a whole typechecks, but we get a run-time error: *dynamic scope makes the type system unsound!*
- Early versions of LISP used dynamic scope, and it is arguably useful in an untyped language.
- Dynamic scope is now generally acknowledged as a mistake, though present in e.g. JavaScript, Python

# Anonymous, first-class functions

- In many languages (including Java as of version 8), we can also write an expression for a function without a name:

$$\lambda x : \tau.\ e$$

- Here, $\lambda$ (Greek letter lambda) introduces an anonymous function expression in which $x$ is bound in $e$.
  - (The $\lambda$-notation dates to Church's higher-order logic (1940); there are several competing stories about why $\lambda$ is used.)
- In Scala one writes: `(x: Type) => e`
- In Java 8: `x -> e` (no type needed)
- In Haskell: `\x -> e` or `\x::Type -> e`
- The *lambda-calculus* is a model of anonymous functions

# Types for the $\lambda$-calculus

- We define $\mathsf{L}_{\mathsf{Lam}}$ to be $\mathsf{L}_{\mathsf{Let}}$ extended with typed $\lambda$-abstraction and application as follows:

$$\begin{array}{rcl} e & ::= & \cdots \mid e_1\ e_2 \mid \lambda x{:}\tau.\ e \\ \tau & ::= & \cdots \mid \tau_1 \to \tau_2 \end{array}$$

- $\tau_1 \to \tau_2$ is (again) the type of *functions from* $\tau_1$ *to* $\tau_2$.
- We can extend the typing rules as follows:

**$\boxed{\Gamma \vdash e : \tau}$ for $\mathsf{L}_{\mathsf{Lam}}$**

$$\frac{\Gamma, x{:}\tau_1 \vdash e : \tau_2}{\Gamma \vdash \lambda x{:}\tau_1.\ e : \tau_1 \to \tau_2} \qquad \frac{\Gamma \vdash e_1 : \tau_1 \to \tau_2 \quad \Gamma \vdash e_2 : \tau_1}{\Gamma \vdash e_1\ e_2 : \tau_2}$$

# Evaluation for the $\lambda$-calculus

- Values are extended to include $\lambda$-abstractions $\lambda x.\ e$:

$$v ::= \cdots \mid \lambda x.\ e$$

(Note: We elide the type annotations when not needed.)

- and the evaluation rules are extended as follows:

**$e \Downarrow v$ for $\mathsf{L}_{\mathsf{Lam}}$**

$$\frac{}{\lambda x.\ e \Downarrow \lambda x.\ e} \qquad \frac{e_1 \Downarrow \lambda x.e \quad e_2 \Downarrow v_2 \quad e[v_2/x] \Downarrow v}{e_1\ e_2 \Downarrow v}$$

- Note: Combined with `let`, this subsumes named functions! We can just define `let fun` as "syntactic sugar"

$$\texttt{let fun}\ f(x{:}\tau) = e_1\ \texttt{in}\ e_2 \iff \texttt{let}\ f = \lambda x{:}\tau.\ e_1\ \texttt{in}\ e_2$$

# Examples

- In $\mathsf{L}_{\mathsf{Lam}}$, we can define a higher-order function that calls its argument twice:

$$\texttt{let fun } \mathit{twice}(f : \tau \to \tau) = \lambda x{:}\tau.\ f(f(x)) \texttt{ in } \cdots$$

- and we can define the composition of two functions:

$$\texttt{let } \mathit{compose} = \lambda f{:}\tau_2 \to \tau_3.\ \lambda g{:}\tau_1 \to \tau_2.\ \lambda x{:}\tau_1.\ f(g(x)) \texttt{ in } \cdots$$

- Notice we are using repeated $\lambda$-abstractions to handle multiple arguments

# Recursive functions

- However, $\mathsf{L}_{\mathsf{Lam}}$ still cannot express general recursion, e.g. the factorial function:

  $$\texttt{let fun } \mathit{fact}(n\texttt{:int}) = \\ \quad \texttt{if } n == 0 \texttt{ then } 1 \texttt{ else } n \times \mathit{fact}(n-1) \texttt{ in } \cdots$$

  is not allowed because *fact* is not in scope inside the function body.
- We can't write it directly as a $\lambda$-expression $\lambda x{:}\tau.\ e$ either because we don't have a "name" for the function we're trying to define inside $e$.
  - (Technically, we could get around this problem in an *untyped* version of the lambda calculus...)

# Named recursive functions

- In many languages, named function definitions are recursive by default. (C, Python, Java, Haskell, Scala)
- Others explicitly distinguish between nonrecursive and recursive (named) function definitions. (Scheme, OCaml, F#)

```
let f(x) = e      // nonrecursive:
                  // only x is in scope in e
let rec f(x) = e  // recursive:
                  // both f and x in scope in e
```

- Note: In the *untyped* $\lambda$-calculus, `let rec` is *definable* using a special $\lambda$-term called the *Y combinator*

# Anonymous recursive functions

- Inspired by $\mathsf{L}_{\mathsf{Lam}}$, we introduce a notation for anonymous *recursive* functions:

$$e ::= \cdots \mid \texttt{rec}\ f(x : \tau_1) : \tau_2.\ e$$

- Idea: $f$ is a local name for the function being defined, and is in scope in $e$, along with the argument $x$.
- We define $\mathsf{L}_{\mathsf{Rec}}$ to be $\mathsf{L}_{\mathsf{Lam}}$ extended with `rec`.
- We can then define `let rec` as syntactic sugar:

$$\texttt{let rec}\ f(x{:}\tau_1) : \tau_2 = e_1\ \texttt{in}\ e_2 \iff \texttt{let}\ f = \texttt{rec}\ f(x{:}\tau_1) : \tau_2.\ e_1\ \texttt{in}\ e_2$$

- Note: The outer $f$ is in scope in $e_2$, while the inner one is in scope in $e_1$. The two $f$ bindings are unrelated.

# Anonymous recursive functions: typing

- The types of $\mathsf{L}_{\mathsf{Rec}}$ are the same. We just add one rule:

**$\boxed{\Gamma \vdash e : \tau}$ for $\mathsf{L}_{\mathsf{Rec}}$**

$$\frac{\Gamma, f : \tau_1 \to \tau_2, x : \tau_1 \vdash e : \tau_2}{\Gamma \vdash \texttt{rec}\ f(x{:}\tau_1) : \tau_2.\ e : \tau_1 \to \tau_2}$$

- This says: to typecheck a recursive function,
  - bind $f$ to the type $\tau_1 \to \tau_2$ (so that we can call it as a function in $e$),
  - bind $x$ to the type $\tau_1$ (so that we can use it as an argument in $e$),
  - typecheck $e$.
- Since we use the same function type, the existing function application rule is unchanged.

# Anonymous recursive functions: semantics

- Like a $\lambda$-term, a recursive function is a value:

$$v ::= \cdots \mid \texttt{rec}\ f(x).\ e$$

- We can evaluate recursive functions as follows:

**$e \Downarrow v$ for $\mathsf{L}_{\mathsf{Rec}}$**

$$\frac{}{\texttt{rec}\ f(x).\ e \Downarrow \texttt{rec}\ f(x).\ e}$$

$$\frac{e_1 \Downarrow \texttt{rec}\ f(x).\ e \quad e_2 \Downarrow v_2 \quad e[\texttt{rec}\ f(x).\ e/f, v_2/x] \Downarrow v}{e_1\ e_2 \Downarrow v}$$

- To apply a recursive function, we substitute the argument for $x$ and the whole `rec` expression for $f$.

# Examples

- We can now write, typecheck and run *fact*
  - (you will implement an evaluator for $L_{Rec}$ in Assignment 2 that can do this)
- In fact, $L_{Rec}$ is *Turing-complete* (though it is still so limited that it is not very useful as a general-purpose language)
- (*Turing complete* means: able to simulate any *Turing machine*, that is, any computable function / any other programming language. ITCS covers Turing completeness and computability in depth.)

# Mutual recursion

- What if we want to define mutually recursive functions?
- A simple example:

```
def even(n: Int) = if n == 0 then true else odd(n-1)
def odd(n: Int) = if n == 0 then false else even(n-1)
```

  Perhaps surprisingly, we can't easily do this!
- One solution: generalize `let rec`:

  `let rec` $f_1(x_1{:}\tau_1) : \tau_1' = e_1$ `and` $\cdots$ `and` $f_n(x_n{:}\tau_n) : \tau_n' = e_n$ `in` $e$

  where $f_1, \ldots, f_n$ are all in scope in bodies $e_1, \ldots, e_n$.
- This gets messy fast; we'll revisit this issue later.

# Summary

- Today we have covered:
  - Named functions
  - Static vs. dynamic scope
  - Anonymous functions
  - Recursive functions
- along with our first "composite" type, the function type $\tau_1 \to \tau_2$.
- Next time
  - Data structures: Pairs (combination) and variants (choice)